

**MATERIAL SAFETY DATA SHEET:VOLTZ II RED****DATE OF ISSUE:** 02/06/2004**SUPERCEDES:** 09/11/2003**SECTION I - GENERAL INFORMATION****Chemical Name & Synonyms:**

N/A

**Trade Name & Synonyms:**

VOLTZ II RED

**Chemical Family:**

ALIPHATIC/LIMONENE BLEND

**Formula Mixture:** X**Manufacturer's Name:**

CHEMSEARCH DIV. OF NCH CORP.

**Address:**

BOX 152170

IRVING, TX 75015

**Prepared By:**

L Boynton/Chemist

**Product Code Number**

0849

**Emergency Phone Number**

800-424-9300

**SECTION II - HAZARDOUS INGREDIENTS**

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

<b>Chemical Name (Ingredients)</b>	<b>Hazard</b>	<b>TLV</b>	<b>PEL</b>	<b>STEL</b>	<b>CAS #</b>
D-LIMONENE	IRRITANT	N/E 1.	N/E 2.	N/E	5989-27-5
1-TETRADECENE	IRRITANT	5 MG/M3\$ 1	5 MG/M3\$ 2	10MG/M3\$ 1	1120-36-1
1-DODECENE	IRRITANT	5 MG/M3\$ 1	5 MG/M3\$ 2	10MG/M3\$ 1	112-41-4
1-OCTADECENE	IRRITANT	5 MG/M3\$ 1	5 MG/M3\$ 2	10MG/M3\$ 1	112-88-9
1-HEXADECENE	IRRITANT	5 MG/M3\$ 1	5 MG/M3\$ 2	10MG/M3\$ 1	629-73-2
\$ AS OIL MIST					

**SECTION III - PHYSICAL DATA**

<b>Boiling Point (f):</b>	463°	<b>Specific Gravity (H2O=1):</b>	0.776
<b>Vapor Pressure (MM HG):</b>	0.16	<b>Color:</b>	RED-ORANGE
<b>Vapor Density (Air=1):</b>	5.0	<b>Odor:</b>	ORANGE
<b>PH @ 100% :</b>	N/A	<b>Clarity</b>	TRANSPARENT
<b>% Volatile by Volume:</b>	100	<b>Evaporation Rate (BU A/C=1):</b>	0.01
<b>H2O Solubility:</b>	NEGLIGIBLE	<b>Viscosity:</b>	NON-VISCOUS

**SECTION IV - FIRE AND EXPLOSION HAZARD**

<b>Flash Point:</b>	<b>Flammable Limits:</b>	<b>LEL:</b>	<b>UEL:</b>
>200°F / SETAFLASH	PRODUCT MIXTURE	0.3%	6.1%

**Extinguishing Media:**

Foam:X Alcohol Foam: CO2:X Dry Chemical:X Water Spray:X Other:

**Special Fire Fighting Procedures:**

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

**Unusual Fire and Explosion Hazards:**

THE USE OF WATER SPRAY (FOG) WHILE EFFECTIVE, MAY CAUSE FROTHING AND FOAMING. NEVER USE A WATER JET AS THIS WILL JUST SPREAD THE FIRE.

**NFPA Hazard Rating: (0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)**

Health:1

Flammability:1

Instability:0

Special:

**SECTION V - HEALTH HAZARD DATA****Threshold Limit Value:**

5 MG/M3 AS OIL MIST 1.

**Effects of Overexposure:****-Acute(Short Term Exposure)**

EYE CONTACT: CAUSES IRRITATION SUCH AS REDNESS AND TEARING. SKIN CONTACT: CAUSES IRRITATION SEEN AS ITCHING AND REDNESS. MAY CAUSE ALLERGIC SKIN REACTION SEEN AS DELAYED SKIN RASH WHICH MAY BE FOLLOWED BY BLISTERING, SCALING, AND OTHER SKIN EFFECTS. PROLONGED OR REPEATED CONTACT AS FROM CLOTHING WET WITH MATERIAL MAY CAUSE DRYING, DEFATTING, AND CRACKING OF THE SKIN. INHALATION: MAY CAUSE RESPIRATORY IRRITATION SEEN AS COUGHING AND SNEEZING. MAY CAUSE ALLERGIC RESPIRATORY REACTION. AT HIGH VAPOR CONCENTRATIONS, INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS HEADACHE, DIZZINESS, DROWSINESS, WEAKNESS, UNCONCIOUSNESS, POSSIBLE ANESTHETIC EFFECTS FROM CENTRAL NERVOUS SYSTEM DEPRESSION, AND MAY BE FATAL. INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA. INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL.

**-Chronic (Long Term Exposure)**

ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO HYDROCARBON MIST POSES A RISK OF CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGHING ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO PULMONARY EDEMA AND HEMORRHAGE AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATION AND HEART RATES AS WELL AS A BLUISH DISCOLORATION OF THE SKIN. CHRONIC SKIN CONTACT MAY PROMOTE DERMATITIS AND OIL ACNE. MAY CAUSE SKIN AND RESPIRATORY SENSITIZATION IN SOME INDIVIDUALS. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS. TARGET ORGANS: LUNGS, CENTRAL NERVOUS SYSTEM, BLOOD-FORMING ORGANS. THE PRIMARY ROUTES OF EXPOSURE ARE SKIN AND EYE CONTACT.

**Primary Routes of Entry:**

Inhalation:X

Ingestion:

Absorption:X

**Emergency and First Aid Procedures:****-Inhalation:**

REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

**-Eye Contact:**

RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING WITH PLENTY OF WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

**-Skin Contact:**

WASH AFFECTED AREAS WITH LARGE AMOUNTS OF SOAP AND WATER FOR 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE.

**-Ingestion:**

GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT GIVE ANYTHING BY MOUTH TO A CONVULSING OR UNCONSCIOUS PERSON.

**-Notes to Physician:**

INGESTION AND SUBSEQUENT VOMITING OF THIS PRODUCT CAN LEAD TO ASPIRATION OF THE PRODUCT INTO THE LUNGS WHICH CAN CAUSE DAMAGE AND MAY BE FATAL. DEPENDING ON THE AMOUNT INGESTED AND RETAINED AS WELL AS THE TOXICITY OF THE PRODUCT, GASTRIC LAVAGE SHOULD BE CONSIDERED. KEEP PATIENT'S HEAD BELOW HIPS TO PREVENT PULMONARY ASPIRATION. IF COMATOSE, A CUFFED ENDOTRACHEAL TUBE WILL PREVENT ASPIRATION.

---

**SECTION VI - TOXICITY INFORMATION****Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By:**

IARC: No

NTP: No

OSHA: No

ACGIH: No

OTHER: No

VOC CONTENT: 100% BY WEIGHT; 100% BY VOLUME; 776 G/L  
LOW VAPOR PRESSURE VOC CONTENT: 4.0% BY WEIGHT

**D-LIMONENE**

ORL-RAT LD50: &gt;5 G/KG 3.

SKN-RBT LD50: &gt;5 G/KG 3.

SKN-RBT: SEVERELY IRRITATING 3.

EYE-RBT: SEVERELY IRRITATING 3.

**1-TETRADECENE**  
**NO TOXICITY DATA AVAILABLE**

**1-DODECENE**  
**NO TOXICITY DATA AVAILABLE**

**1-OCTADECENE**  
**NO TOXICITY DATA AVAILABLE**

**1-HEXADECENE**  
**SKN-RBT LD: >10 G/KG 4.**  
**ORL-RAT LD: >10 G/KG 4.**  
**IHL-RAT LC: >8500 MG/M3/1H 4.**

**HYDROCARBON MISTS ARE REPORTED TO HAVE LOW ACUTE AND SUB-ACUTE TOXICITIES IN ANIMALS. EFFECTS FROM SINGLE SHORT-TERM REPEATED EXPOSURES TO HIGH CONCENTRATIONS OF MISTS WELL ABOVE APPLICABLE WORKPLACE EXPOSURE LEVELS INCLUDE LUNG INFLAMMATORY REACTION, LIPOID GRANULOMA FORMATION, AND LIPOID PNEUMONIA.**

---

#### **SECTION VII - REACTIVITY DATA**

**Stability:** Stable:X Unstable:  
Conditions to Avoid: NONE KNOWN.

**Incompatibility (Materials to Avoid):**

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE; ACIDIC AGENTS AND CLAYS, ALUMINUM CHLORIDE, HALOGENS, IODINE PENTAFLUORIDE, VINYL CHLORIDE, AND SOME PLASTICS AND RUBBER.

**Hazardous Decomposition Products:**

OXIDES OF CARBON.

**Hazardous Polymerization:** May Occur: Will Not Occur:X  
Conditions to Avoid: N/A

---

#### **SECTION VIII - SPILL OR LEAK PROCEDURES**

**Steps to be Taken if Material is Released or Spilled:**

WEAR APPROPRIATE PROTECTIVE CLOTHING. USE CARE AS SPILLS MAY BE SLIPPERY. DIKE AND CONTAIN SPILL. ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. PREVENT PRODUCT FROM CONTAMINATING SOIL OR FROM ENTERING SEWAGE AND DRAINAGE SYSTEMS AND BODIES OF WATER. FLUSH AREA WITH WATER.

**Waste Disposal Method(s):**

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

**Neutralizing Agent:**

N/A

---

#### **SECTION IX - SPECIAL PROTECTION INFORMATION**

**Required Ventilation:**

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE EXCESSIVE LEVELS OF VAPORS OR MISTS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

**Respiratory Protection:**

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR 1910.134) AND ANSI'S STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACEPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND IN PUBLICATION NO. 87-116 OR ANSI Z88.2-1992.

**Glove Protection:**

NEOPRENE OR NITRILE RUBBER GLOVES SHOULD BE WORN. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

SAFETY GLASSES WITH SIDE SHIELDS IF THE METHOD OF USE PRESENTS THE LIKELIHOOD OF EYE CONTACT. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

WEAR PROTECTIVE CLOTHING WHEN HANDLING. REMOVE SOAKED CLOTHING AND SHOES. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE.

<b>Storage Temperature:</b>	Indoors:X	Outdoors:	Heated:	Refrigerated:
Minimum Temperature:35°F		Maximum Temperature:120°F		

ALWAYS STORE MATERIAL IN ITS ORIGINAL CONTAINER. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUES WHICH MAY EXHIBIT THE HAZARDS OF THE PRODUCT. TO AVOID POSSIBLE EXPLOSION DO NOT PRESSURIZE, CUT, WELD, SOLDER, DRILL, GRIND, OR EXPOSE EMPTY CONTAINERS TO HEAT. HOT SURFACES. SPARKS. OR OPEN FLAMES.

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

Those Ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

PLEASE CALL 1-800-527-9919 FOR ADDITIONAL INFORMATION IF YOU ARE A CALIFORNIA CUSTOMER.

THIS MSDS IS NOT INTENDED FOR USERS IN THE STATE OF CALIFORNIA

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES. ACGIH. 2003.

- ## 2. OSHA PEL

- ### 3. VENDOR'S MSDS.

- 4. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFOWeb, 2003.**

ALL THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR OTHERWISE EXEMPTED FROM LISTING.

-----IRR:IRRITANT, FLAM/FLAMM:FLAMMABLE,  
 COMB:COMBUSTIBLE, CORR:CORROSIVE CARC:CARCINOGENIC, TOX:TOXIC, N/A:NOT APPLICABLE, N/E:NOT  
 ESTABLISHED, COC:CLEVELAND OPEN CUP, PMCC:PENSKY-MARTIN CLOSED CUP, TCC:TAGLIABUE CLOSED  
 CUP.

LEL:LOWER EXPLOSION LIMIT, UEL:UPPER EXPLOSION LIMIT, NFPA:NATIONAL FIRE PROTECTION ASSOCIATION, IARC:INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP:NATIONAL TOXICOLOGY PROGRAM, OSHA:OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH:AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV:THRESHOLD LIMIT VALUE, PEL:PERMISSIBLE EXPOSURE LIMIT, STEL:SHORT-TERM EXPOSURE LIMIT, MLD:MILD, MOD:MODERATE, SEV:SEVERE, MUT:MUTAGENIC, ASPHYX:ASPHYXIAANT, PNOS:PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, SDT:STANDARD DRAIZE TEST, ORL:ORAL, IHL:INHALATION, HMN:HUMAN

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product."