

Spartan Chemical Company, Inc. Material Safety Data Sheet

Redicing from Betcher Co.

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

SPRAYBUFF

Product Number: 3040; 4440

trial

Product Division: Janitorial

Spartan Chemical Company, Inc. 1110 Sparton Drive

Maumee OH 43537

Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Buffing, polishing compounds, liquid, n.o.s.

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: I- Slight
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z-1-A			
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m²	CEILING mg/m²	NTP, IARC or OSHA Carcinogen
Ethylene-acrylic acid copolymer Nonyl phenol ethoxylate	1-5 1-5	9010-77-9 9016-45-9	Not Established Not Established	Not Established Not Established	Not Established Not Established	No No

SECTION III: PHYSICAL DATA

Bolling Point: 212 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Linknown	Solubility in Water: Complete
pH: 10.0 - 10.5	Specific Gravity (H,O=1): 0.996
Evaporation Rate (but.ace,=1): <1	Percent Solid by Weight: 3-4
Physical State: Liquid	
Appearance & Odor: Milky light blue liquid, faint odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combustion.	Use extinguishing media appropriate for surrounding fire.
wear NIOSH approved self-contained	breathing apparatus and protective clothing. Cool fire-exposed
Unusual Fire & Explosive Hazards: Material can splatter above 212 F. Dr	ied Product can burn. Combustion products are toylo

ECTION V: HEALTH HAZARD DAT	Ά.				
Threshold Limit Value			1	of Entry: Inhalation, Skin Contact, Eyes and Oral.	
Effects of Overexposure	- May cause mli	d eye irritation with sy	mptoms such as pain, re	iness, swelling and tearing.	
Conditions to Avoid	void: May cause mild skin irritation with symptoms such as redness, pain and swelling. May be harmful if swallowed with symptoms such as nausea, vomiting, pain and diarrhea. Inhalation of product mist may cause respiratory irritation.				
	Avoid contra	roduct mist may cause	e respiratory irritation.		
	with adams	it with eyes, skin or	ciothing. Avoid breath	ing product mist. Do not swallow, Us	
Conditions Aggregated by Use	Wich adequa	te ventilation. Wasi	h thoroughly after han	dling.	
conditions Aggravated by Ose	dermatitis.	oduct may aggravate p	reexisting eye; skin and	respiratory disorders such as asthma and	
Emergency & First Aid Procedure	S:				
Eyes	Flush eyes wit	h plenty of water for a	it least 15 minutes. Rem	Ove contact lenses. Cet modical attention	
Skin	Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention. Remove contaminated clothing. Flush skin with water for at least 15 minutes. Get medical attention if				
	imitation persi	sts. Wash contaminati	ed clothing before reuse.		
Ingestion:	Do not induce	vomiting. Drink one o	or two glasses of water to	dilute product. Get medical attention. Do	
	not give anytr	ing by mouth to an un	iconscious person.		
Inhalation:	In case of resp	piratory irritation or diz	ziness; move person to f	resh air. Get medical attention if irritation	
	persists.				
CTION VI: REACTIVITY DATA					
Stability:	Stable		Incompatible Ma	aterials: Strong oxidizing agents.	
Hazardous Decomposition Products:	Thermal decon	position may yield rylic monomers.	Hazardous Polymer	Izadon: Will Not Occur.	
Steps to be Taken in Case Material is Released or Spilled:	Small spills of permitted by k			f water to sanitary sewer system (If spills with inert material and transfer liquid	
	w containers i	or recovery or discussion		spins with their material and transfer liquid	
Waste Disposal Method:	Assure conform	nance with federal, sta	te and local regulations.		
CTION VIII; SPECIAL PROTECTI	ON INFORMAT	TION			
Respiratory Protection:	Not normally n	eeded when good vent	tilation is provided		
Ventilation:	Provide good c	eneral ventilation Loc	en) automorphism (Carlotter		
Protective Gloves(Specify Type):	Pubbos or othe	refrence de la company	ai exhaust ventilation ma	be necessary for some operations.	
Eye Protection(Specify Type):	Splace secolor	impervious gioves ar	e recommended for proid	inged or repeated contact.	
Other Protective Equipment	Splash goggles or safety glasses are recommended to prevent eye contact. For further guidance see 29 CFR 1910.132-138.				
Cote: Frocecave Equipment;	For turmer guid	Jance see 29 CFR 1910	0.132-138.		
CTION IX: SPECIAL PRECAUTION	1S			· · · · · · · · · · · · · · · · · · ·	
Precautions; Handling & Storing:	Keen from free:	daa .			
Other Precautions:	Keep out of rea	ch of children			
		- ar armorett			
5 SCC 06/30/2005	Name:	Ronald T. Cook	Title:	**·	
PRAYBUFF	EF Frotting Date: 06/20/2002	Manager, Regulatory Affairs			
A6. 70 CEN 1018 1000 1000 1	Changes:		Supercedes:	09/27/2004	
·· ·· · · · · · · · · · · · · · ·	-1011349;	Update Section XI			

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.